



EPS BOX-TP

THREE-PHASE



- PC+ABS, Robust plastic enclosure IP65
- Applied to residential, commercial solar installations
- Used with AIO H3 inverter
- Automatically switch to On-Grid/Off-Grid state



Max. input current
(per phase) 32A



Safety



IP65
Rated



Easy
Installation



For more information about the Fox ESS range, visit
www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	EPS BOX-TP
GIRD INPUT	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
AC Frequency [Hz]	50 / 60
Max. Input Current (per Phase) [A]	32
EPS INPUT	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
AC Frequency [Hz]	50 / 60
Max. Input Current (per Phase) [A]	25
EPS LOAD	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
AC Frequency [Hz]	50 / 60
Max. Output Current [A]	32
GENERAL DATA	
Cooling Concept	Natural
Installation	Wall-mounted
Operating Temperature Range [°C]	-25 ~ +50
Dimensions (W*H*D) [mm]	340 * 223 * 170
Net Weight [kg]	2.8
Ingress Protection	IP65

