



# Smart Meter

SINGLE-PHASE/THREE-PHASE



## SIMPLE & EASY

LCD display, easy to set and check



## ENERGY EFFICIENT

Overall power consumption  $\leq 1$  W



## ACCURATE

Class 1 measurement accuracy

## TECHNICAL SPECIFICATIONS

MODEL	DDSU666	DTSU666	DTSU666 1.5(6)A 200A CT
<b>GENERAL DATA</b>			
Dimension (W*H*D) [mm]	36*85*66	72*100*85	72*100*85
Mounting type		DIN35 Rail	
Weight (including cables) [kg]	1.2	1.5	1.5
<b>POWER SUPPLY</b>			
Power grid type	1P2W	3P4W	3P4W
Input voltage (phase voltage) [Vac]		176 ~ 288	
Power consumption [W]	$\leq 0.8$	$\leq 1$	$\leq 1$
<b>MEASUREMENT RANGE</b>			
Line voltage [Vac]	/	304 ~ 499	304 ~ 499
Phase voltage [Vac]		176 ~ 288	
Current [A]	0 ~ 60	0 ~ 80	0 ~ 200
<b>MEASUREMENT ACCURACY</b>			
Voltage [%]		$\pm 0.5$	
Current / Power / Energy [%]		$\pm 1$	
Frequency [Hz]		$\pm 0.01$	
<b>COMMUNICATION</b>			
Interface		RS485	
Baud rate [bps]		9600	
<b>ENVIRONMENT</b>			
Operating temperature range [°C]		-25 ~ +55	
Storage temperature range [°C]		-40 ~ +70	
Operating humidity [%RH]		5 ~ 95 (Non-condensing)	
<b>OTHERS</b>			

Accessories

/

/

3 CT 200A(1m)

